



技术参数 SPECIFICATIONS

- ◆ 极数: 20、30、40、50
- ◆ Poles: 20、30、40、50
- ◆ 额定电压: AC, DC, 50V
- ◆ Rated voltage: AC, DC, 50V
- ◆ 额定电流: 1.0A AC, DC
- ◆ Rated Current: 1.0A AC, DC
- ◆ 耐压值: 500V AC/minute
- ◆ Withstand voltage: 500V AC/minute
- ◆ 工作温度: -25° C ~ +85° C
- ◆ Working Temperature: -25° C ~ +85° C
- ◆ 绝缘电阻: ≥100 MΩ
- ◆ Insulation resistance: ≥100 MΩ
- ◆ 接触电阻: ≤20mΩ
- ◆ Contact resistance: ≤20mΩ

材料 MATERIAL  
 ◆ HOUSING: Nylon, UL94V-0 (White)

包装方式 PACKAGE  
 ◆ 袋装 Bag Package

Cir-cuits	Part No.	Dimensions(mm)			Qty/bag
		A	B	C	
20	1.0T-2-20Y	9.0	11.0	13.6	1,000
30	1.0T-2-30Y	14.0	16.0	18.6	1,000
40	1.0T-2-40Y	19.0	21.0	23.6	1,000
50	1.0T-2-50Y	24.0	26.0	28.6	1,000

 旭森实业(深圳)有限公司 JUSUN INDUSTRIAL (SHENZHEN) CO.,LTD.]		GENERAL TOLERANCE		SCALE		DRAWN		DATE		DWG. NO.		TITLE		REV.	
		XX ± 0.25	XXX ± 0.40	5=1	CHECK	2009.11.17	E:\DWG\Production\	塑胶图		A					
X ± 0.20	.XXX ± 0.05	UNIT	MM	APPROVE	DATE	PARTS NO.		DATE		1.0T-2-NY		SHEET		1/1	
X ± 0.15	X° ± 2°	SIZE	A4		2009.11.17			2009.11.17							
.XX ± 0.08	X° ± 1°				2009.11.17										